


SRQ Series

Radial EDLC Cell 引线式EDLC 单体

Typical applications 典型应用

- Intelligent instruments: electronic, water, gas and heat meters
- Communication terminals: RTU/DTU, DTU, FTU, fault-current indicators
- Consumer products: toys, robots, smart-home and medical devices
- Auto electronics: recorders, door/audio controls, diagnosis systems, wireless charging
- Energy storage: server backup, motor drives, brake/charging piles, security, fire protection



Branding illustration / 品牌外观示意

Electrical characteristics 电气特性

Parameter / 项目	Specification / 规格
Rated voltage / 额定电压	2.7 V
Operating temperature / 工作温度	-40 to +85 °C
Surge voltage / 浪涌电压	2.85 V
Capacitance range / 容量范围	1-50 F
Capacitance tolerance at 25 °C / 容量偏差	-10% to +30%


Reliability characteristics 可靠性特性

Test / 项目	Condition / 条件	Requirements / 要求
Temperature characteristics 温度特性	-40 to +85 °C -40 至 +85 °C	Capacitance change: within 30% of initial value at 25 °C ESR _{AC} : "4 × initial specified value 容量变化: 30% 以内; 内阻: ≤4 倍
High-temperature load 高温负荷	Rated voltage, 85 °C, 1,000 h 额定电压, 85 °C, 1,000 小时	Capacitance change: within 30% of initial value ESR _{AC} : "4 × initial specified value 容量变化: 30% 以内; 内阻: ≤4 倍
High-temperature storage 高温存储	85 °C, 1,000 h 85 °C, 1,000 小时	Capacitance change: within 30% of initial value ESR _{AC} : "4 × initial specified value 容量变化: 30% 以内; 内阻: ≤4 倍
Cycle life 循环寿命	500,000 cycles, 25 °C V _R to ½V _R 500,000 次充放电循环, 25 °C	Capacitance change: within 30% of initial value ESR _{AC} : "4 × initial specified value 容量变化: 30% 以内; 内阻: ≤4 倍

SRQ Series

Radial EDLC Cell 引线式EDLC 单体

Dimensions 外形尺寸



Dimensions in mm. Tolerances are shown in the drawing.

Ratings and part numbers 额定值与料号

U _R (Surge Voltage) Code 额定电压 (浪涌电压) 代码	Rated Cap. 25°C 额定容量 25°C	Impedance 内阻		Leakage Current 漏电流(72hrs)	Size 尺寸 $\Phi D \times L$	Weight 重量	P/N 产品代码
		ESR _{DC} 直流内阻	ESR _{AC} 交流内阻 (1KHz)				
(V)	(F)	(mΩ)	(mΩ)	(mA)	(mm)	(g)	-
2.7 (2.65) 2R7	1	800	400	0.008	8 x 14	0.9	SCCDQR2R7105QRH080014EP
	2	320	160	0.010	8 x 14	1.0	SCCDQR2R7205QRH080014EP
	3	160	80	0.012	8 x 20	1.4	SCCDQR2R7305QRH080020EP
	3.3	160	80	0.012	8 x 20	1.4	SCCDQR2R7335QRH080020EP
	5	160	80	0.016	10 x 20	2.2	SCCDQR2R7505QRH100020EP
	7	120	60	0.020	10 x 25	2.7	SCCDQR2R7705QRH100025EP
	10	180	90	0.030	10 x 25	2.8	SCCDQR2R7106QRH100025EP
	10	100	50	0.030	10 x 30	3.2	SCCDQR2R7106QRH100030EP
	10	100	50	0.030	12.5 x 20	3.4	SCCDQR2R7106QRH125020EP
	15	70	35	0.045	12.5 x 25	4.3	SCCDQR2R7156QRH125025EP
	20	50	25	0.060	12.5 x 30	5.2	SCCDQR2R7206QRH125030EP
	25	50	25	0.080	16 x 25	7.4	SCCDQR2R7256QRH160025ET
	50	40	20	0.140	18 x 40	13.8	SCCDQR2R7506QRH180040ET